

For release: September 2010

News Release

NOW YOU CAN HAVE STUDIO CAMERA QUALITY WITH P2 RECORDING

Hitachi CR-P2HD high performance P2HD recorder

Hitachi Kokusai Electric is displaying its CR-P2HD high performance P2HD recording adaptor for its high-performance portable HDTV cameras (SK-HD1000 and Z-HD5000) at IBC (Stand No: B50 Hall 11, RAI Centre, Amsterdam, 10-14 September 2010).



“The compact CR-P2HD P2HD recording adaptor delivers high-speed access and instantaneous recording start. High definition audio and video can be recorded for approximately 128 minutes when using two AVC-Intra 100 64GB P2 cards. Plus, the unit has low power consumption, is robust and resistant to extreme temperatures. With its two built in P2 slots and a 3.5 inch colour LCD monitor, audio and video recordings on the P2 card can be reviewed instantaneously”, said Richard Harvey of Hitachi Kokusai.

The adaptor records both 1080i and 720p video formats and 48kHz/16 bit x 4 channel audio. It features HD-SDI digital video and analogue audio outputs as standard, as well as USB2.0 and IEEE1394 connections.

The CR-P2HD is designed to work exclusively with Hitachi’s popular HD SK-HD1000 and Z-HD500 cameras and enables them to work as completely independent field recording cameras – giving the studio manager additional configuration flexibility and work flow efficiency. Plus, when docked to the Hitachi HDTV cameras, the system provides a low center of gravity which makes it both comfortable and easy to use for long periods of time. The system delivers excellent value for money and return on investment.

Full specifications are below.

Ends

News Release

P2 Adaptor CR-P2HD Specifications

P2 Adaptor CR-P2HD Specifications					
1	Recording Format	AVC-Intra 100 / 50 DVCPRO HD	9	Power	DC12V (DC10.5~17.0V)
2	Video signal	1080 / 59.94i , 50i 720 / 59.94P , 50P	10	Power consumption	17W
3	Audio signal	48kHz/16bit x 4ch	11	Operating Temperature	0~40℃
4	Recording Media	P2 Card /2 slots	12	I/O	HD-SDI OUT,VIDEO OUT TC IN/OUT , GL IN DC IN/OUT , MIC IN AUDIO OUT IEEE1394 IN /OUT, USB2.0 (HOST,DEVICE)
5	Recording Playback Time AVC-Intra 100 AVC-Intra 50	When using 64GB P2card x 2 slot Approx. 128 minutes Approx. 256 minutes			
6	LCD Monitor	3.5" color LCD	13	Dimensions(mm) Weight	143(W) x 189(H) x 185(D) 3.5kg
7	Wireless Microphone Receiver	Azden "Slot-in" (option)	14	Microphone Holder (for SK-HD1000/ Z-HD500 cameras)	MH-1000 for long Mic(optional) MH-402 for short Mic(optional)
8	Battery Mounting Plate	IDX or Anton-Bauer type (specify when ordering)			

About Hitachi Broadcast

Hitachi Broadcast is the broadcast technology department of Hitachi Kokusai Electric Europe GmbH in EMEA. Hitachi Kokusai Electric Europe GmbH is a wholly owned subsidiary of Hitachi Kokusai Electric Inc Tokyo, Japan.

For more information:

Hitachi Kokusai Electric Europe GmbH
Frankfurt office: Cemal Yilmaz c.yilmaz@hitachi-keu.com
London office: Paddy Roache paddy@hitachi-keu.com
www.hitachi-keu.com

For media information:

Red Cell
 Tel: 01376 561666
 Email: ask@redcell.info
www.redcell.info